

XP-002265613

BEST AVAILABLE COPY

AN - 1994-245670 [30]

AP - JP19920334528 19921215; [Previous Publ. JP6179644] ; JP19920334528
19921215

CPY - MITU

DC - E16

DR - 0245-S 0270-S 0343-S 0347-S 1391-S

FS - CPI

IC - B01J23/02 ; B01J27/04 ; B01J27/08 ; B01J27/25 ; B01J31/02 ; B01J31/04 ;
B01J31/08 ; C07B61/00 ; C07C231/08 ; C07C233/18

MC - E10-D03C N01-A N04-C N04-D N05-E02 N05-E03

M3 - [01] H5 H581 H8 J0 J011 J3 J371 K0 L6 L640 M210 M211 M212 M213 M214
M215 M216 M220 M221 M222 M223 M224 M225 M226 M231 M232 M233 M272 M281
M312 M321 M331 M340 M342 M383 M391 M416 M620 M720 M903 M904 N242 N243
N261 N262 N333 N342 N362 N441 N511 N512 N513; 9430-C3801-P
- [02] A100 A103 A111 A119 A940 C017 C101 C108 C316 C540 C550 C730 M411
M414 M416 M730 M903 Q421

PA - (MITU) MITSUBISHI KASEI CORP

PN - JP3182946B2 B2 20010703 DW200139 C07C231/08 005pp
- JP6179644 A 19940628 DW199430 C07C233/18 006pp

PR - JP19920334528 19921215

XA - C1994-111915

XIC - B01J-023/02 ; B01J-027/04 ; B01J-027/08 ; B01J-027/25 ; B01J-031/02 ;
B01J-031/04 ; B01J-031/08 ; C07B-061/00 ; C07C-231/08 ; C07C-233/18

AB - J06179644 Prepn. of N-(alpha-alkoxyethyl)formamide (I) is effected by
reaction of N-(alpha-hydroxyethyl)formamide (II), obtd. by reaction of
formamide (III) with acetaldehyde in the presence of basic catalyst,
with prim. or sec. alcohols in the presence of acidic catalyst. (III)
contains below 1000 ppm diformamide.

- Pref. acetaldehyde contg. less than 300 ppm acetic acid is used.
Purified (I) is obtd. by distn. of (I) under reduced pressure (max.
temp. is 70-100 deg.C and the max. pressure is 2-30 mmHg). In the
prepn. of (II), the salt of strong alkali e.g. hydroxide of alkali
metal (Li, Na or K etc.) and weak acid e.g. organic acid, phenols or
sulphurous acid etc., is used as basic catalyst. The catalyst is used
in an amt. of 0.01-10 (0.1-5) mol% to (III). The mol ratio of (III) :
acetaldehyde is 1 : 1.0-5.0. The reaction is carried out at (-)10-100
(0-40) deg.C. The prim. or sec. alcohol e.g. methanol, ethanol, etc.
is used in an amt. of 1.0-30 times mol to (II). Acidic catalyst e.g.
H2SO4 or HCl etc. is used in an amt. of 0.001-10 (0.1-5) mol%. The
reaction is carried out at (-)10-60 (0-40) deg.C.

- USE/ADVANTAGE - (I) is a useful material as an intermediate in the
prepn. of N-vinylformamide. (I), which has good thermal stability, is
obtd. in high yield (95-97%).(Dwg.0/0)

CN - 9430-C3801-P

IW - PREPARATION N ALPHA ALKOXYETHYL FORMAMIDE N VINYL FORMAMIDE REACT N
ALPHA HYDROXYETHYL FORMAMIDE OBTAIN FORMAMIDE ACETALDEHYDE PRIMARY SEC
ALCOHOL PRESENCE ACIDIC CATALYST

IKW - PREPARATION N ALPHA ALKOXYETHYL FORMAMIDE N VINYL FORMAMIDE REACT N
ALPHA HYDROXYETHYL FORMAMIDE OBTAIN FORMAMIDE ACETALDEHYDE PRIMARY SEC
ALCOHOL PRESENCE ACIDIC CATALYST

NC - 001

OPD - 1992-12-15

ORD - 1994-06-28

PAW - (MITU) MITSUBISHI KASEI CORP

TI - Prepn. of N-(alpha-alkoxyethyl)-formamide used for N-vinyl- formamide
- by reacting N-(alpha-hydroxyethyl)-formamide obtd. from formamide
and acetaldehyde with prim. or sec. alcohol in presence of acidic
catalyst

BEST AVAILABLE COPY